## **MISTRIP**

## <P>Small pitch, LED pixel strip</P><br>









MiSTRIP, Barco's creative pixel strip, can be used in a wide variety of applications, from large free-form video displays to architectural visual design. Thanks to its high brightness and tight pixel pitch in a slim, lightweight yet rugged package, the MiSTRIP is a true all-round performer. The possibilities with MiSTRIP are endless, from stunningly bright video displays of any size, shape or form to lighting effects. In addition, the MiSTRIP's IP65 protection rating and wide operating temperature range enable outdoor usage in any weather conditions.





Product specifications	MISTRIP
Pixel pitch	13.25 mm
Brightness	160 cd/m
Calibrated Brightness	6100 Nit
Viewing angle	145° symmetrical
Operating temperature	-20°C -> 45°C
Operating humidity	10 - 90%
LED configuration	3-in-1 SMD RGB
Lifetime	50,000 hours
Colors	185 Trillion
Processing	15.8 bit / color
Refresh rate	800 Hz
Connections	d-Sub 25
Mounting	Multiple movable M6 threads on integrated track
D320 input compatibility	Data DVI up to UXGA, SDI, HD-SDI, YUV, Composite, S-Video
Height	26 mm
Depth	excl. connector: 55 mm
Depth	incl. connector: 63 mm
Length	1484 mm / 375 mm
Certifications	ETL (UL equivalent), CEBEC, CE, FCC Class A

